

## **HARDWARE FEATURES**

- Stainless steel envelope
- Counter-weighted vertical sliding door
- In-line strainer
- LED Lighted chamber
- Multiple fixtures available
- Casters for easy installation

### **RESULTING IN...**

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

## **SOFTWARE FEATURES**

- Patent-pending AUTOMAT3D™ platform
- Proprietary *Agitation Algorithms*
- Variable temperature (85-160°F, 29-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

### **RESULTING IN...**

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details

## **PRODUCT SPECIFICATIONS**

### **SIZE AND WEIGHT**

- Envelope: 19" L x 27.5" W x 26" H  
(48 cm x 70 cm x 66 cm)
- Machine Footprint (Closed door):  
– 44.7" L x 40.4" W x 93.8" H  
(114 cm x 103 cm x 238 cm)
- Machine Footprint (Open door):  
– 105" L x 82" W x 100" H  
(267 cm x 208 cm x 254 cm)
- Approx. Weight: 1200 lbs. (544 kg) empty,  
1370 lbs. (621 kg) full



### **ELECTRICAL**

#### **US:**

- Voltage: 208V 3 Phase
- Amperage: 30A
- Connector: HBL530P9W

#### **EU:**

- Voltage: 400V 3 Phase
- Amperage: 15A
- Connector: HBL 516P6W

### **CONSUMABLES**

- Detergent: PLM-101-SPRAY for Polyjet  
PLM-201-SPRAY for FDM

### **SAFETY FEATURES**

- Emergency stop
- Auto-interrupt
- Compliant with all OSHA regulations
- **CE**

### **MATERIALS AND TECHNOLOGIES**



FDM



POLYJET

#### **POSTPROCESS TECHNOLOGIES INC.**

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### **POSTPROCESS TECHNOLOGIES INTERNATIONAL**

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13

#### **TRIMECH**

4461 Cox Road, Suite 302, Glen Allen, VA 23060  
Marketing@TriMech.com TriMech.com 888.874.6324